

再生资源处理装备

鹰嘴剪 Hydraulic Power Shear

适用对象: 大型钢材拆解作业。

主要特点: 采用瑞典Hardox Hituf钢材, 韧性好、耐磨;
销轴采用42CrMo合金钢, 强度高、韧性好;
采用瑞士进口旋转马达, 扭矩大、转速快;
大油缸采用珩磨管, 进口NOK油封, 工作周期短, 寿命长;
刀块采用耐磨合金钢, 抗高温、耐变形。

Applicable object: disassembly of large steel.
Main features: Made of Swedish Hardox Hituf steel, good toughness and wear resistance;
The pin is made of 42CrMo alloy steel with high strength and toughness;
Rotary motor imported from Switzerland, high torque and fast speed;
Big oil cylinder adopts honing tube, imported NOK oil seal, short working cycle and long life;
The knife block is made of wear-resistant alloy steel, which is resistant to high temperature and deformation.



项目/型号 Item/Model	单位 Unit	JSPS180	JSPS250	JSPS350	JSPS450
小臂安装 Arm Installation	ton	13-17	18-27	28-39	40-50
大臂安装 Boom Installation	ton	10-12	14-18	20-28	28-39
重量 Weight	kg	1100	2100	3500	4900
最大张幅 Maximum Opening With Jaw	mm	375	485	620	700
总长度 Overall Length	mm	2100	2700	3280	3700
驱动压力 Operating Pressure	kg/cm ²	250-300	250-300	280-320	320-350
驱动油量 Operating Flux	L/min	90-110	180-220	200-250	250-300

再生资源处理装备

液压吸盘 Excavator Magnet Lift

适用对象: 铁制品物料装卸、搬运作业。

主要特点: 采用Q345锰板钢材, 强度高、耐腐蚀;
半永久设计, 减少管路维护费用。

Applicable objects: loading and unloading of iron products and handling operations.
Main features: using Q345 manganese plate steel, high strength and corrosion resistance;
Semi-permanent design reduces pipeline maintenance costs.



再生资源处理装备

抓料机 Sorting Grab

适用对象: 各种大型、散装物料装卸或搬运作业。

主要特点: 采用Q345锰板钢材, 强度高、耐腐蚀;
销轴采用42CrMo合金钢, 强度高、韧性好;
采用瑞士进口旋转马达;
油缸采用珩磨管, 进口HALLITE油封, 工作周期短、寿命长。

Applicable object: all kinds of large-scale, bulk materials loading and unloading or handling operations.
Main features: using Q345 manganese plate steel, high strength and corrosion resistance;
The pin is made of 42CrMo alloy steel, with built-in oil passage, high strength and good toughness;
Rotary motor imported from Switzerland;
The oil cylinder adopts honing tube, imported HALLITE oil seal, short working cycle and long life.



项目/型号 Item/Model	单位 Unit	JSSG04	JSSG06	JSSG08	JSSG10
适用挖掘机 Suitable Excavator	ton	6-12	12-18	18-25	25-32
重量 Weight	kg	470	1050	1370	1700
工作容量 Operating Capacity	m ³	0.60	0.60	0.80	1.00
A	mm	1730	2175	2700	3300
B	mm	960	1200	1500	1880
C	mm	595	745	935	1160
H	mm	1350	1700	2100	2650
H1	mm	1570	1970	2400	3080
驱动压力 Driving Pressure	kg/cm ²	300	300	300	300
驱动油量 Operating Flux	L/min	180-230	180-230	200-250	250-300
旋转马达 Rotating Motor	设置压力 Set Up Pressure	kg/cm ²	120	120	120
	油量 Motor Flux	L/min	30	30	30
	旋转速度 Frequency	r/min	16-18	16-18	16-18

功能辅助装备

拇指夹 Hydraulic Power Thumb

适用对象: 物料抓取辅助作业。

主要特点: 采用Q345锰板钢材, 强度高、耐腐蚀;
油缸采用珩磨管, 进口HALLITE油封, 工作周期短、寿命长。

Applicable object: auxiliary operation for material grabbing.
Main features: using Q345 manganese plate steel, high strength and corrosion resistance;
The oil cylinder adopts honing tube, imported HALLITE oil seal, short working cycle and long life.

